DEALER HOT WATER PRESSURE WASHERS
Portable Electric
Belt Drive | HHS Series

Hanson Industrial Inc.

The best way to tackle the toughest cleaning job is with the HHS Series of pressure washers. Completely portable, easy to use and one of the most reliable in the industry.

HHS-2004-2E2G

Pump
- *Belt drive triplex piston AR or General pump*
- *Adjustable high pressure detergent injector*

Motor
- *Open drip-proof electric motor with thermal overload protection*
- *35-foot power cord*

Frame
- *Wrinkle-finish powder coated steel frame assembly*
- *13-inch flat-free tires with rear tire brake*

Components
- *Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil*
- *No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)*
- *Auto start/stop*
- *Time delay shutdown*
- *Hour meter*
- *10-gallon polyethylene fuel tank*
- *Racor fuel filter/water separator*
- *Wand holder*
- *Adjustable thermostat*
- *Polyethylene float tank with inlet filter screen*

Miscellaneous
- *Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F*

Unit Includes:
- *Quick connect nozzles – 0°, 15°, 25°, 40° and low pressure nozzle*
- *50-foot x ⅜-inch high pressure hose with quick connects*
- *Adjustable pressure insulated dual lance*
- *Professional-grade insulated trigger gun with safety lock-off*

Made in USA with Globally Sourced Components

Exclusive Dealer Product

C US CSA CERTIFIED

All models except HHS-3005-2E2G HHS-3005-2E8G

Hanson Industrial Inc. • 4743 41st Street, Moline, IL 61265 • (800) 345-0903 • (309) 762-3302 • www.hansonindustrial.com

DEALER HOT WATER PRESSURE WASHERS
Portable Electric
Belt Drive | HHS Series

Hanson Industrial Inc.

Model Number	*PSI*	*GPM*	*Horsepower/Motor*	*Pump*	*Plug Type*	*Burner Fuel Tank Capacity*	*Fuel Consumption*	*BTU per hour*	*Dimensions (LxWxH)*	*Ship Wt.*	*Net Wt.*
HHS-1003-2E1G	1000	2.8	2.0 HP, 115V, 1Ø, 20.0A	General	NEMA 5-20P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	610 lb.	490 lb.
HHS-2004-2E2A	2000	4.2	6.0 HP, 230V, 1Ø, 28.0A	AR	NEMA 6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E2G	2000	4.2	6.0 HP, 230V, 1Ø, 28.0A	General	NEMA 6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E3G	2000	4.2	6.0 HP, 230V, 3Ø, 18.5A	General	NEMA L15-20P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E4G	2000	4.2	6.0 HP, 460V, 3Ø, 12.0A	General	NEMA L16-20P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E8G	2000	4.2	6.0 HP, 208V, 1Ø, 29.9A	General	NEMA 6-50P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-2004-2E9G	2000	4.2	6.0 HP, 208V, 3Ø, 21.0A	General	NEMA L15-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
HHS-3004-2E2A	3000	3.9	8.0 HP, 230V, 1Ø, 39.5A	AR	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E2G	3000	3.9	8.0 HP, 230V, 1Ø, 39.5A	General	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E3G	3000	3.9	8.0 HP, 230V, 3Ø, 22.5A	General	NEMA L15-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E4G	3000	3.9	8.0 HP, 460V, 3Ø, 14.0A	General	NEMA L16-20P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	720 lb.	600 lb.
HHS-3004-2E5G	3000	3.9	8.0 HP, 575V, 3Ø, 12.0A	General	NEMA L17-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	720 lb.	600 lb.
HHS-3004-2E8G	3000	3.9	8.0 HP, 208V, 1Ø, 43.0A	General	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3004-2E9G	3000	3.9	8.0 HP, 208V, 3Ø, 25.5A	General	NEMA L15-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
HHS-3005-2E2G	3000	4.8	10.0 HP, 230V, 1Ø, 46.5A	General	NEMA 6-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
HHS-3005-2E3G	3000	4.8	10.0 HP, 230V, 3Ø, 27.5A	General	NEMA L15-30P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
HHS-3005-2E4G	3000	4.8	10.0 HP, 460V, 3Ø, 16.5A	General	NEMA L16-20P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	724 lb.	604 lb.
HHS-3005-2E5G	3000	4.8	10.0 HP, 575V, 3Ø, 14.0A	General	NEMA L17-30P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	724 lb.	604 lb.
HHS-3005-2E8G	3000	4.8	10.0 HP, 208V, 1Ø, 50.7A	General	NEMA 6-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
HHS-3005-2E9G	3000	4.8	10.0 HP, 208V, 3Ø, 31.5A	General	NEMA L15-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.

Options:

Part Number	*Description*	*Fits Models*
HX-0162	**Stainless-steel bottom wrap** - Converts powder coated painted bottom wrap to stainless-steel	All models
HX-0171	**Skid feet** - Stationary applications	All models
HX-0172	**250°F steam** - Increases outlet temperature to 250°F	HHS-3004 models
HX-0174	**250°F steam** - Increases outlet temperature to 250°F	1000 & 2000-PSI models
HX-0176	**250°F steam** - Increases outlet temperature to 250°F	HHS-3005 models
HX-0196	**Skid frame/roll cage design** - Stationary applications	All models
HX-0248	**Wireless remote** - EZ-quip install	All models
HX-0254	**K7 unloader, flow activated (Auto start/stop N/A)** - Converts pressure trapping unloader system to flow actuated K7 unloader	HHS-2004 & HHS-3004 models
HX-0255	**K7 unloader, flow activated (Auto start/stop N/A)** - Converts pressure trapping unloader system to flow actuated K7 unloader	HHS-3005 models

Accessories:

Part Number	*Description*	*Fits Models*
50-0170	**Stack adapter** - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	**Gasket (for 50-0170)** - Seals between 50-0170 stack adapter and boiler housing	All models

NEMA 5-20P, 20-amp plug

NEMA 6-30P, 30-amp plug

NEMA 6-50P, 50-amp plug

NEMA L15-30P, 30-amp plug

NEMA L15-20P, 20-amp plug

NEMA L15-50P, 50-amp plug

NEMA L16-20P, 20-amp plug

NEMA L17-30P, 30-amp plug